



EXPRESS MAIL CERTIFICATE

Date 5/13/02 Label No. EV028720461-45

I hereby certify that, on the date indicated above, this paper or fee was deposited with the U.S. Postal Service & that it was addressed for delivery to the Assistant Commissioner for Patents, Washington, DC 20231 by "Express Mail Post Office to Addressee" service.

PLEASE CHARGE ANY DEFICIENCY UP TO \$300.00 OR CREDIT ANY EXCESS IN THE FEES DUE WITH THIS DOCUMENT TO OUR DEPOSIT ACCOUNT NO. 04-0100

B.W. LEE B.W. Lee  
Name (Print) Signature

Customer No.:



07278

PATENT TRADEMARK OFFICE

Docket No.: 3391/0G343 US0

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: Guy Reina  
Serial No.: 10/057,751  
Confirmation No.: 9515  
Filed: January 24, 2002  
For: AN EFFICIENT FFT IMPLEMENTATION FOR ADSL

PRELIMINARY AMENDMENT

Hon. Commissioner of  
Patents and Trademarks  
Washington, DC 20231

Sir:

Prior to the examination of the above-identified application, please amend the application as follows:

## IN THE CLAIMS

Please amend the claims as follows:

1. (Amended) A method for extending a dynamic range of a communication signal used in performing an FFT process, comprising the steps of:

obtaining a first communication signal comprising a set of data points, the first communication signal having a set of signal characteristics;

enabling an output division of the data points at each output stage of the FFT process during a first communication signal transmission;

determining a maximum output communication signal sampled during the first communication signal transmission;

predicting a maximum output communication signal for a second signal transmission using the signal characteristics of the first communication signal during the first communication signal transmission;

calculating a number of unnecessary output divisions for each output stage of the FFT process during the second signal transmission using the number of unnecessary output divisions determined from the predicted maximum output communication signal in the predicting step and the maximum output communication signal sampled during the first communication signal transmission in the determining step; and

selectively disabling the output stage division for at least one output stage of the FFT process during the second signal transmission in accordance with the number of unnecessary output divisions determined in the calculating step.

Please add the following new claims 2-21:

2. (New) A method as in claim 1, wherein the enabling step divides the communication signal data points utilizing a divide and conquer approach.
3. (New) A method as in claim 2, wherein the divide and conquer approach is at least one of decimation in time and decimation in frequency.
4. (New) A method as in claim 1, wherein the FFT process comprises at least one of a radix-2 butterfly FFT, radix-4 butterfly FFT, and a split-radix butterfly FFT process.
5. (New) A method as in claim 1, wherein the FFT system comprises at least one of a fixed-point and integer FFT process.
6. (New) A method as in claim 1, wherein the predicting step determines the maximum output signal for a second signal transmission according to the following relationship:

$$R = 2^{(M-1)-D-G-H}$$

wherein R represents a value approximately equal to or greater than the maximum output signal for the second signal transmission; M represents a number of bits in a data storage word; D represents a maximum difference in bit usage among a set of communication signals; G represents a maximum allowed gain change; and H represents headroom.

7. (New) A method as in claim 6, wherein the predicting step further comprises sampling the first communication signal for M, D, G, and H values.

8. (New) A method as in claim 6, wherein M, D, G, and H are fixed FFT process values.

9. (New) A method as in claim 6, wherein H is approximately 0.5 bits.

10. (New) A method as in claim 6, wherein M is approximately 16.

11. (New) A method as in claim 6, wherein D is approximately 1.5 bits.

12. (New) A method as in claim 6, wherein G is approximately 0.5 bits.

13. (New) A method as in claim 1, wherein the calculating step determines the number of unnecessary output divisions for each output stage of the FFT process for the second signal transmission according to the following relationship:

$$s = \text{floor} \left( \log_2 \left( \frac{R}{|B_m|} \right) \right)$$

wherein s represents the number of unnecessary output divisions for each output stage of the FFT process for the second signal transmission; R represents the predicted maximum output signal for a second signal transmission;  $B_m$  represents the maximum output communication signal sampled during the first signal transmission; and floor represents a function that returns an integer value.

14. (New) A system for extending a dynamic range of a communication signal in an FFT process, comprising:

an FFT module having a plurality of selectively disabled output stage divisions;

a shift control module connected to the output stage divisions of the FFT through a control line which disables the output stage divisions of the FFT; and

an optimized shift calculator connected to the shift control module through a command line, the optimized shift calculator determining a number of unnecessary output divisions and instructing the shift control module to disable corresponding number of output stage division;

wherein the optimized shift calculator determines the number of unnecessary output divisions according to the following relationship:

$$s = \text{floor} \left( \log_2 \left( \frac{R}{|B_m|} \right) \right)$$

wherein  $s$  represents the number of unnecessary output divisions;  $B_m$  represents a maximum output communication signal sampled during a first signal transmission;  $R$  represents a predicted maximum output signal for a second signal transmission; and floor represents a function that returns an integer value.

15. (New) A system as in claim 14, wherein  $R$  is determined according to the following relationship:

$$R = 2^{(M-1) \cdot D \cdot G \cdot H}$$

wherein M represents a number of bits in a data storage word; D represents a maximum difference in bit usage among a set of communication signals; G represents a maximum allowed gain change; and H represents headroom.

16. (New) A system as in claim 15, wherein M, D, G, and H are fixed FFT system values.

17. (New) A system as in claim 14, wherein the control line of the shift control module disables each output division stage of the FFT module in a serial manner.

18. (New) A system as in claim 14, wherein the shift control module further comprises at least two control-lines, a first control line for disabling a first output division stage and a second control line for disabling a second output division stage, wherein the first control line and the second control line disable each output division stage concurrently.

19. (New) A method for extending a dynamic range of a communication signal used in an FFT system having a set of output stage divisions, comprising the steps of:

calculating a number of unnecessary output divisions for each output stage of FFT system during a second signal transmission period using a maximum output communication signal sampled during a first communication signal transmission period and a number of unnecessary output divisions determined from a predicted maximum output communication signal for the second signal transmission; and

selectively disabling the output stage division for at least one output stage of the FFT system during a second signal transmission in accordance with the number of unnecessary output divisions determined in the calculating step.

20. (New) A method as in claim 19, wherein the calculating step determines the number of unnecessary output divisions for each output stage of the FFT system for the second signal transmission period according to the following relationship:

wherein  $s$  represents the number of unnecessary output divisions for each output state of the FFT system during the second signal transmission;  $R$  represents the predicted maximum output signal for a second signal transmission;  $B_m$  represents the maximum output communication signal sampled during the first signal transmission; and  $\text{floor}$  represents a function that returns an integer value.

21. (New) A method as in claim 19 wherein, the calculating step determines the maximum output signal for a second signal transmission according to the following relationship:

$$R = 2^{(M-1)-D-G-H}$$

wherein  $R$  represents a value approximately equal to or greater than the maximum output signal for the second signal transmission;  $M$  represents a number of bits in a data storage word;  $D$  represents a maximum difference in bit usage among a set of communication signals;  $G$  represents a maximum allowed gain change; and  $H$  represents headroom.



REMARKS

Claim 1 has been amended. New claims 2-21 have been added. No new matter has been added. Support for the claim amendment to claim 1 and the new claims can be found on page 7, line 22- page 9, line 7 and page 10, line 19 - page 11, line 12 of the specification as filed.

An early and favorable action on the merits is respectfully requested.

Respectfully submitted,

Lisa J. Ulrich  
Registration No. 45,168  
Attorney for Applicant

DARBY & DARBY, P.C.  
Post Office Box 5257  
New York, N.Y. 10150-5257  
Phone (212) 527-7700

20057751-051302





# MARK-UP CLAIMS FOR PRELIMINARY AMENDMENT

In re Application of Guy Reina

Serial No. 10/057,751

Filed: January 24, 2002

For: AN EFFICIENT FFT IMPLEMENTATION FOR ADSL

1. (Amended) A method [in an FFT system] for extending a dynamic range of a communication [signals] signal [in communication devices] used in performing an FFT process, comprising the steps of:

obtaining a first communication signal[, the communication signal] comprising a set of data points, the first communication signal having a set of signal characteristics;

enabling an output division of the [communication signal] data points[, the output division enabled] at each output stage of the FFT [system] process during a first communication[s] signal transmission;

determining a maximum output communication signal sampled during the first communication signal transmission;

predicting a maximum output communication signal [during] for a second signal transmission using the signal characteristics of the first communication signal during the first communication[s] signal transmission;

calculating a number of unnecessary output divisions for each output stage of the FFT [system] process during the second signal transmission[, using the number of unnecessary output divisions determined from the predicted maximum output communication signal in the

10057751.054302

predicting step and [from] the maximum output communication signal sampled during the first communication signal transmission in the determining step; and

selectively disabling [selectively] the output stage division for at least one output stage of the FFT [system] process during the second signal transmission [using] in accordance with the number of unnecessary output divisions determined in the calculating step.

2025-07-10 10:57:51